

# Antenna Design Strategy and Demonstration for SDR

Taeyoung Yang, William A. Davis, Warren L. Stutzman,  
S.M. Shajedul Hasan, Randall Nealy, Carl B. Dietrich, Jeff H. Reed

{mindlink, wadavis, stutzman, hasan, rnealy, cdietric, reedjh} @ vt.edu

Prepared for SDR '10

December 3<sup>rd</sup>, 2010, Session 7B: RF, IF, ADC, *Regency D*,  
08:30 "Antenna Design Strategy and Demonstration for Software-Defined Radio" (Best of R&D Track)

**Wireless @ Virginia Tech** (<http://wireless.vt.edu>)  
Bradley Department of Electrical and Computer Engineering  
Blacksburg, VA

- 1 -

## Outline

### 1. Motivation

### 2. Ant. Design Challenges

- Radiation Physics
- Fundamental Limit on Size & Performance
- Size Miniaturization Techniques

### 3. Ant. Design Strategy for SDR

### 4. Demonstration


- 2 -

## Motivation

Push Harder !!!



SDR



Bottleneck ...



Limited by radiation physics principles, not technology

- 3 -

## Antenna Radiation Physics


Inside Radian Sphere

→ Energy storage process dominant

Outside Radian Sphere

→ Radiation process dominant

Radian Sphere




Physics requires  
a minimum amount  
of non-radiating energy

- 4 -



# Antenna Radiation Physics - II



- 5 -


# Fundamental-Limit Theory

## Frontiers

- H.A. Wheeler, 1947
- L.J. Chu, 1948

## Basic Assumptions

- Passive LTI system
- Antenna is enclosed in minimum sphere (*antenna sphere*)
- Antenna structure has all-pass-filter characteristics
- Spherical-mode excitation



## Radiation Q




Connect to Impedance-Matching Limit

$$Q_{rad} = e_r \frac{[W_{non-rad}]_{peak}}{\langle P_{rad} \rangle / \omega} \approx \frac{f_c}{BW_{3dB}} \text{ for single-resonant antenna}$$

- 6 -

# Fundamental-Limit Theory: Ideal Antenna → Minimum $Q_{rad}$


## • Two-Port Ideal Antenna Model (Chu's Circuit)



### • High-Pass Filter Characteristic


### • Relatively Constant Gain above Cut-off frequency

### • For example, TM<sub>1</sub> Fundamental Mode →




- 7 -

# Theoretical-Limit versus Reality



$$Q_{rad, Chu}^{min} = e_r \frac{(1 + 2k^2 a^2)}{(k^3 a^3)(1 + k^2 a^2)}$$

$$Q_{rad, VTAG}^{min} = e_r \frac{1}{k^3 a^3}$$




$$k = \frac{2\pi}{\lambda}$$

- 8 -



## Real Antenna Problem



- 9 -

## Antennas for SDR

### ☐ Resonant

- ✓ **Smallest form factor** → **Best for handheld devices**
- ✓ **To resolve impedance-matching / Narrow BW issues**
  - Resistive loading ( $e_r \downarrow$ )
  - Reconfigurable (Switching speed? ; power consumption  $\uparrow$ )
  - Multi-band (complexity  $\uparrow$ )
- ✓ **To resolve varying radiation-pattern issue over operational freq.**
  - Traps

### ☐ Frequency-independent

- ✓ **Wide bandwidth, but not instantaneous (dispersive)**
  - **Best for 'fixed'-channel radio**
- ✓ **Directional patterns (high directivity)**


### ☐ Ultra-wideband

- ✓ **Wide instantaneous bandwidth**
  - **Best for dynamic freq. agile functions**
- ✓ **Directional or omni-directional patterns**
- ✓ **Size issues** → Tradeoffs


- 10 -

## "Impulse" Response of Antennas


Monopole




Log-Periodic



Rigid TEM



Half-Disk



- 11 -

## SDR Antenna Design Challenges

Antenna  
Design

Limits

How  
Antenna  
Works?




- Size
- Performance
- Function
- Cost

Tradeoffs !

- 12 -



# Antenna Design Strategy Based on Fundamental-Limit Theory



- If  $ka \geq 1$ ,
  - Set  $Z_0 = Z_{\text{wave}}$  for maximum BW
  - Otherwise, need impedance trans.
  - Best for freq.-agile functions
- If  $ka < 1$  (electrically small),
  - Tune antenna for maximum gain
  - Add loss for wide BW

→ Antenna Size & function need to be defined at initial stage of system design

- 13 -



## Ant. Miniaturization Techniques

### □ Impedance Loading

- BW limitations

### □ Material Loading

- Just  $\epsilon_r \uparrow$  or  $\mu_r \uparrow \rightarrow \text{Size} \downarrow \text{ \& BW} \downarrow$
- Both  $\epsilon_r \uparrow$  &  $\mu_r \uparrow \rightarrow \text{Size} \downarrow$  with same BW
  - Usually, heavy and lossy
  - Not available at high freq.



### □ Slow-wave Structural Patterns

- Usually drops gain
- Easy to get smaller size & maintain BW




### □ Negative Impedance Converter (NIC) → Stability issues

### □ Engineered/Meta Materials → Narrow BW & efficiency issues


- 14 -

# Antenna Design Strategy to Get Around Fundamental-Limit Theory

**Fundamental-Limit Theory**  
→ Instantaneous BW




**Continuous Wide BW with Multiple Resonances**



$$Q_{r,INS} \leq Q_{r,MR}$$

- 15 -

## The Targeted SDR Platform




- ✓ Developed in Wireless@VT
- ✓ Direct conversion radio using Motorola RFIC
- ✓ 100 MHz - 4 GHz operational frequency range with a 9 kHz to 20 MHz channel bandwidth

- 16 -




## Compact UWB Antenna for SDR – I



### □ Preliminary Specifications


- Size: 3" High
- Instantaneous BW: 450 MHz – 6 GHz
- Realized Gain: 5 dBi
- Form Factor: Hemispherical



- 17 -

## Compact UWB Antenna for SDR – II

- ✓ Measured radome material characteristics:  $\epsilon_r = 2.53$ ,  $\tan\delta = 0.01$
- ✓ Silver paint



Initial Design





2<sup>nd</sup> Prototype

- 18 -

## Compact UWB Antenna for SDR - III


- ✓ Instantaneous BW: From 433 MHz to ???
- ✓ Electrical Size:  $0.11 \lambda$  @ 433 MHz
- ✓ Radiation Pattern: Omni-directional in azimuth with LP



- \* **Commercial Hybrid Code (FEM + MoM): FEKO Suite v5.5**  
(<http://www.feko.info>)

- 19 -

## Compact UWB Antenna for SDR - IV




- ✓ Instantaneous BW: From 433 MHz to 20 GHz (46:1 BW)

- 20 -



## Compact UWB Antenna for SDR - V

- Measured Impulse Response for 50-ps Gaussian input pulse



- ✓ Extremely narrow pulse radiation
- ✓ Linear Phase over entire band → Instantaneous BW !

- 21 -

## Prototype Antenna In DEMO Session



### OSSIE/GNU Radio Generic Component Demonstration

- Duyun Chen (University of Pennsylvania)
- Garrett Vanhoy (University of Arizona)
- Marypat Beaufait (University of Michigan)
- Carl B. Dietrich (Virginia Tech)

- 22 -

## Conclusion

### □ Ant. Design Challenges

- ✓ Antenna Radiation Physics  
    → Minimum non-radiating energy
- ✓ Limitations on Size and Performance → Tradeoffs
- ✓ Miniaturization Techniques → Loading

### □ Ant. Design Strategy for SDR

- ✓ Beyond the Classic Fundamental Limit ← Concept
- ✓ Size Criteria to Choose Antenna Type
- ✓ Resonant (smallest), Frequency-independent (directivity), Ultra-wideband (instantaneous) antennas

### □ Demonstration – Compact UWB antenna

- 23 -

## Next Step

### □ Add Reconfigurable functions

- ✓ Both instantaneous BW (above Cut-off Freq.)  
    + tunable BW (below Cut-off Freq.)  
    with the Same Form Factor
- ✓ Radiation Pattern Reconfigurability:  
    Omni or Directional Pattern
- ✓ Polarization Reconfigurability:  
    Linear or Circular Polarization
- ✓ Receiving Near Vertical Incident Signal (NVIS)

- 24 -