



Distributed Localized Interference Avoidance for Dynamic Frequency Hopping ad hoc Networks



Sebastian Koslowski, Jens
Elsner, Friedrich K. Jondral



Stefan Couturier



Cédric Keip, Olaf Bettinger

Communications Engineering Lab
Prof. Dr.rer.nat. Friedrich K. Jondral



KIT – Universität des Landes Baden-Württemberg und
nationales Forschungszentrum in der Helmholtz-Gemeinschaft

www.kit.edu



Outline

- CORASMA project overview
- CORASMA simulator
 - Basic Waveform
 - Network structure
 - Channels and Slots
- Interference Avoidance
 - Basic idea and example
 - Hopset adaption
 - Spectrum sensing
- Markov model and results
- Conclusion

Project overview



- **CORASMA: COgnitive RAdio for dynamic Spectrum MAnagement**
 - Consortium: Thales (FR, GE, BE, IT), MUT, Saab, Selex, Tekever
 - Projected Duration: Nov. 2010 – Nov. 2013
 - Funded by the European Defense Agency (EDA)

- Key topics addressed:
 - Cognitive radio in military context
 - Dynamic spectrum allocation
 - Spectrum usage optimization
 - High-fidelity system simulations


- Main objective: design of a **high-fidelity platform for tactical network simulation including PHY/MAC/NET protocol stack running in a realistic propagation environment**

CORASMA simulator



- Basic Waveform (BW)
 - Fully functional waveform (within the simulation framework)
 - Common basis for different cognitive solutions


- Cognitive Manager(s)
 - One cognitive solution per partner
 - Each solution extends some part of the basic waveform by a cognitive process
 - Using a common spectrum sensing module



Basic Waveform



- Clustered network structure
 - Nodes are grouped into clusters
 - Operating on separate channels
 - Cluster heads manage access
 - Gateway nodes allow for inter-cluster communication

- Multi-channel MAC
 - Network-wide control channel (Random Access Slots, RAS)
 - Cluster-wide control channels (Cluster head signaling slot, CHSS)
 - Data Slots (DATA)





Interference Avoidance: Basic idea

- Cognitive extension of the Basic WF
- Frequency hopping over K channels
 - Cluster-based frequency hopping improves robustness and increases security
 - Local orthogonality is preserved
- Dynamic frequency hopping: Do not hop on bad channels
 - Local decision for each cluster
 - Find a different locally unused hopset to substitute a bad channel
 - Coordinate with neighboring clusters



Interference Avoidance: Example



Channels: c1 - c11

Time steps: t1 - t10

Hopsets: 1 - 11



Cluster colors:

Bad channels:

We substitute bad channels with hopsets!

Distributed hopset adaptation protocol

- Coordination / notification of hopset adaptations necessary




- Cluster heads inform their neighbors when adapting their hopsets
- ...and possibly allow them to object (avoiding conflicts)

Spectrum sensing

- Channel exclusion (re-inclusion) by issuing (revoking) substitutions based on the results of spectrum sensing

- Implicit Sensing:
 - During message reception
 - Based on PER or SNR
 - Used to detect bad channels

- Explicit Sensing:
 - While idle / upon request
 - Energy Detection
 - Used to explore excluded channels



- Sensing is performed in collaboration with peer nodes



Outline

- CORASMA project overview
- CORASMA simulator
 - Basic Waveform
 - Network structure
 - Channels and Slots
- Interference Avoidance
 - Basic idea and example
 - Hopset adaption
 - Spectrum sensing
- Markov model and results
- Conclusion



Performance modeling

- A simple simulative model describing the dependencies and the possible gains of dynamic frequency hopping as proposed
 - Qualitative insight for Cognitive Manager design
 - Simple way to verify the behavior of the CORASMA simulator

- Chosen here: Markov model
 - What gains can be expected compared to random hopping?




Markov model


- Goal: A simple simulative model describing the dependencies and the possible gains of dynamic frequency hopping as proposed
- Model assumptions
 - Describes only a one-hop cluster neighborhood
 - Interference is the same in all clusters
 - Substitution protocol works as described, channel is substituted with hopset right away (ideal, fast reaction)
- Model parameters
 - N clusters in K channels
 - Interference starts with probability p_s , ends with probability p_e
 - Success probability for sensing p_d
 - N_e channels can be explicitly sensed in each time step
 - State vectors: **F** (Currently bad channels), **S** (list of substitution hopsets)

Markov model

- The interference model for each channel is based on a simple Markov chain M :




- The simulation states F and S only depend on the last step and also have the Markov property




Markov model results

- Performance gain of hopset adaption vs. random hopping for different interference statistics ($N = 25$, $K = 50$, $N_e = 5$, $p_d = 0.95$)




Markov model results

■ Impact of explicit sensing parameter N_e
($N = 25$, $K = 50$, $p_d = 0.95$)



■ Impact of the network size / node density
($p_s = p_e = 0.05$, $N_e = 5$, $p_d = 0.95$)



Conclusion

- Overview of the CORASMA project
- Combating localized interference in a clustered ad hoc network using Dynamic Frequency Hopping
- Distributed hopset adaption algorithm allowing each cluster to best utilize the available channels
- Simplified Markov model yields a maximal performance gain of two compared to random hopping (for the presented scenarios)



Thank you for your attention. Questions?

Communications Engineering Lab
Prof. Dr.rer.nat. Friedrich K. Jondral



KIT – Universität des Landes Baden-Württemberg und
nationales Forschungszentrum in der Helmholtz-Gemeinschaft

www.kit.edu