



# Cognitive Multi-Radio as Enabler for Deterministic Dynamic Spectrum Access

Wireless Innovation Forum European Conference on Communications Technologies and Software Defined Radio (WInnComm-Europe)

Matej Kloc, Norman Franchi, Markus Gardill, Robert Weigel

Erlangen, 8th October 2015

**Institute for Electronics Engineering**  
University of Erlangen-Nuremberg  
Prof. Dr.-Ing. Dr.-Ing. habil. Robert Weigel  
Prof. Dr.-Ing. Georg Fischer





# Cognitive Multi-Radio as Enabler for Deterministic Dynamic Spectrum Access

Wireless Innovation Forum European Conference on Communications Technologies and Software Defined Radio (WInnComm-Europe)

Matej Kloc, Norman Franchi, Markus Gardill, Robert Weigel

Erlangen, 8th October 2015

**Institute for Electronics Engineering**  
University of Erlangen-Nuremberg  
Prof. Dr.-Ing. Dr.-Ing. habil. Robert Weigel  
Prof. Dr.-Ing. Georg Fischer



# Agenda

1. Motivation
2. Approach – Cognitive Multi-Radio
3. Measurements
4. Evaluation
5. Summary


# Agenda

1. Motivation
2. Approach – Cognitive Multi-Radio
3. Measurements
4. Evaluation
5. Summary

# 1. Motivation

## Industrial Wireless Communications (IWC)

- **Applications**
  - Process control and automation
  - Monitoring
  - Motion control (e.g. in robotics)
- **Short-Real-Time Requirements**
  - High reliability / determinism
  - Low latency
  - Low cycle times (<5 ms) [1,2]
- **Deterministic Dynamic Spectrum Access (D-DSA)**
  - TDMA<sup>1</sup> / time-slotted communication scheme for real-time IWC



- DSA in every time slot required for deterministic transmission of time-critical process data


<sup>1)</sup> TDMA = Time-Division Multiple Access

# 1. Motivation

## Current Situation

### • Problems / Limitations of IWC Systems

- No exclusive frequency band for IWC
- Operation in licence-free frequency bands [3]
  - Primary in 2.4 GHz ISM<sup>1</sup> band (2.40-2.4835 GHz)
  - Highly crowded → coexistence problems
  - Repeated frequency (re-)planning for reliable operation
- Limitations on spectrum access by regulations
  - ETSI EN 300 328 V1.9.1 [4]
  - Listen-before-Talk (LBT) mechanism for broadband and non-FHSS<sup>2</sup> systems required
  - Related works [5] are not considering the updated spectrum regulations
- Current IWC technologies do not provide short-real-time capability
  - e.g. WirelessHART [6] → (fixed) time slot duration of 10 ms



<sup>1</sup>) ISM = Industrial, Scientific and Medical


<sup>2</sup>) FHSS = Frequency Hopping Spread Spectrum

# 1. Motivation

## Short-Real-Time IWC System

### • Solution

- Cognitive Radio (CR) technology for IWC in ISM frequency bands [7-9]
  - Observation of spectrum and adaptation of transmission parameters
  - Efficient utilization of (limited) spectrum resources
- Operation on multiple channels as key enabler for broadband D-DSA under short-real-time requirements with low cycle times (<5 ms) and in presence of various wireless technologies (e.g. WLAN<sup>1</sup> devices)



- Challenge → detection of unoccupied channel & switching during a time slot

<sup>1)</sup> WLAN = Wireless Local Area Network


# Agenda

1. Motivation
2. Approach – Cognitive Multi-Radio
3. Measurements
4. Evaluation
5. Summary

## 2. Approach – Cognitive Multi-Radio

### Transceiver Concept for Short-Real-Time IWC

- Architecture




- Multiple Radio Front Ends (RFEs)
  - Robust Physical Layer (PHY) based on Standard IEEE 802.11p
  - Spectrum Sensing Unit (SSU)
- ➔
- Parallel observation of multiple channels with SSU
  - Rapid channel selection / switching during a time slot (e.g.  $T_{Slot} = 1 \text{ ms}$ )
  - Improvement of D-DSA in ISM band

## 2. Approach – Cognitive Multi-Radio

### Robust Physical Layer (PHY)


- **Standard IEEE 802.11p PHY for IWC [10]**
  - Primary intended for Car2Car / Car2X communications
  - Orthogonal Frequency-Division Multiplexing (OFDM)
    - Multi-carrier (broadband) modulation scheme
- **Why?**
  - High robustness against multi-path propagation
    - Highly reflective industrial environments (e.g. manufacturing hall)
  - Well dimensioned Guard Interval (GI)
    - $T_{GI,802.11p} = 1.6 \mu s > T_{DS,max} = 1.2 \mu s$
  - High adaptability
  - Higher achievable data rates
    - >12x higher than e.g. WirelessHART  
(IEEE 802.15.4)

**Maximum Excess Delay Evaluation [11]**



## 2. Approach – Cognitive Multi-Radio

### Spectrum Access Scheme [12]



- Time-slotted communication scheme incl. Acknowledgement (ACK)
- Implementation of LBT mechanism
- Clear Channel Assessment (CCA) check before every transmission  
→  $T_{Se,C} = 18 \mu s$
- Extended CCA (ECCA)  
→  $18 \mu s \leq T_{Se,E} \leq 160 \mu s$
- Optional retransmission during a time slot when data or ACK frame drops
- Compliance to ETSI EN 300 328 V1.9.1

## 2. Approach – Cognitive Multi-Radio

### Channel Sensing & Modelling

- **Energy Detection**

$$Y_n(k) = \frac{1}{N_{Se}} \sum_{m=k}^{k+N_{Se}} |r_n(m)|^2 \begin{matrix} \geq \\ \approx \\ \leq \end{matrix} \lambda_{th} \begin{matrix} H_1 \\ \\ H_0 \end{matrix} \quad [13]$$


$\lambda_{th}$ : Energy threshold

$r_n$ : Received complex samples on  $n^{\text{th}}$  channel

$N_{Se}$ : Number of sensing samples

- **Markov Model**

- Modelling of traffic in ISM band as a time-discrete Markov chain [14]
- Multi-channel sensing information used for learning the Markov model



$\pi_i$ : Initial probability

$p_{ij}$ : Transition probability


#### Channel with lowest traffic / occupancy

$$\max_n (\hat{d}_{0,n} - \hat{d}_{1,n}) = \max_n \left( \frac{\pi_0}{1-p_{00}} - \frac{\pi_1}{1-p_{11}} \right) \quad [14]$$

with  $n \in \{1, \dots, N_{RFE}\}$

## 2. Approach – Cognitive Multi-Radio

### Channel Selection Strategy



Number of available ('idle') channels

$$0 \leq N_{Ch,A} \leq N_{RFE}$$

# Agenda

1. Motivation
2. Approach – Cognitive Multi-Radio
- 3. Measurements**
4. Evaluation
5. Summary

# 3. Measurements


## For Coexistence Analysis in the 2.4 GHz ISM Frequency Band

- **Focussing on Interferences caused by WLAN IEEE 802.11b/g**

- Laboratory environment at FAU
- Non-overlapping channels in 2.4 GHz ISM band
  - $f_{c,1} = 2.412 \text{ GHz}$  (Ch. 1)
  - $f_{c,2} = 2.437 \text{ GHz}$  (Ch. 6)

- **Measurement Platform**

- Configuration of receivers
  - Carrier frequency:  $f_{c,1}, f_{c,2}$
  - Sampling rate: 10 MSps
  - Reference level: -50 dBm
- Acquisition of I/Q samples




# 3. Measurements

## For Coexistence Analysis in the 2.4 GHz ISM Frequency Band

- Results

- Spectrogramm



→ Measured I/Q samples (channel utilization) used for coexistence analysis

# Agenda


1. Motivation
2. Approach – Cognitive Multi-Radio
3. Measurements
4. Evaluation
5. Summary

# 4. Evaluation


## System Implementation / Configuration

- **MATLAB Implementation**
  - IEEE 802.11p PHY, SSU and MAC
- **Wireless Channel Emulation**
  - Multi-path propagation + AWGN + interference
  - Standardized Rayleigh model
    - JTC<sup>1</sup> (type indoor commercial B) [15]
- **Measured Channel Utilization in the 2.4 GHz ISM Frequency Band used for Coexistence Simulation**

**Discrete Power Delay Profile**



**Baseband Wireless Channel Model**




<sup>1)</sup> JTC = Joint Technical Committee

# 4. Evaluation

## Simulation Results

- **Short-Real-Time Capability**  $Pr(t_{Tx} < 1 \text{ ms})$ 
  - Without interference



- P2P<sup>1</sup> communication scenario
- Payload of 50 bytes
- 2000 time slots per simulation step
- Evaluation of transmission probability during a time slot ( $T_{Slot} = 1 \text{ ms}$ ) in the 2.4 GHz ISM band
- Reduced performance due to transmission errors at low SNR<sup>2</sup>
- Highest performance with  $R_c = 1/2$


<sup>1</sup>) P2P = Point-to-Point

<sup>2</sup>) SNR = Signal-to-Noise-Ratio

# 4. Evaluation

## Simulation Results

- **Short-Real-Time Capability**  $Pr(t_{Tx} < 1 \text{ ms})$ 
  - With interference





→ Performance degradation due to spectrum sharing → limited D-DSA

# 4. Evaluation

## Simulation Results

- Mean Transmission Latency  $\overline{t_{Tx}}$ 
  - With interference



→ Reduction of  $\overline{t_{Tx}}$  by a factor  $>2$

# 4. Evaluation

## Discussion


- **Pro**

- Improvement of D-DSA in ISM bands
- Improvement of short-real-time capability for wireless transmission of process data with stringent timing requirements ( $T_{Slot} = 1 \text{ ms}$ )

- **Contra**

- Higher hardware cost
  - Primary due to multiple RFEs
- Higher energy consumption
  - Due to spectrum sensing and receiving with multiple RFEs

→ Focus of this work on improvement of short-real-time capability of IWC



**With Cognitive Multi-Radio Approach**

# Agenda

1. Motivation
2. Approach – Cognitive Multi-Radio
3. Measurements
4. Evaluation
5. Summary

# 5. Summary

- **Requirements of IWC Systems**
- **Problems / Limitations of current IWC Systems**
  - D-DSA in coexistence-afflicted ISM frequency bands
  - Current IWC technologies do not provide short-real-time capability
- **Approach for Improvement of D-DSA in ISM Bands**
  - Transceiver concept → Cognitive Multi-Radio
  - Spectrum access scheme (compliant to ETSI EN 300 328 V1.9.1)
  - Markov-based channel modelling incl. channel selection strategy
- **Evaluation**
  - Improvement of D-DSA for short-real-time IWC

# References

- [1] A. Frotzsch, U. Wetzker, M. Bauer, M. Rentschler, M. Beyer, S. Elspass and H. Klessig, „Requirements and Current Solutions of Wireless Communication in Industrial Automation,“ in Proc. of IEEE International Conference on Communications Workshops (ICC), 2014.
- [2] M. Weiner, M. Jorgovanovic, A. Sahai and B. Nikolic, „Design of a Low-Latency, High-Reliability Wireless Communication System for Control Applications,“ in Proc. of IEEE International Conference on Communications (ICC), 2014.
- [3] ZVEI, „Coexistence of Wireless Systems in Automation Technology: Explanations on Reliable Parallel Operation of Wireless Radio Solutions,“ 2009.
- [4] ETSI EN 300 328 V1.9.1 - Electromagnetic Compatibility and Radio Spectrum Matters (ERM), 2015.
- [5] K. Kunert, M. Jonsson und U. Bilstrup, „Deterministic Real-Time Medium Access for Cognitive Industrial Radio Networks,“ in Proc. of 9th IEEE International Workshop on Factory Communication Systems (WFCS), 2012.
- [6] J. Song, S. Han, A. Mok, D. Chen, M. Lucas und M. Nixon, „WirelessHART: Applying Wireless Technology in Real-Time Industrial Process Control,“ in Proc. of IEEE Real-Time and Embedded Technology and Applications Symposium (RTAS), 2008.
- [7] J. Mitola and G. J. Maguire, „Cognitive Radio: Making Software Radios More Personal,“ in IEEE Personal Communications, Vol. 6, Issue 4, pp. 13-18, August 1999.
- [8] A. Wilzeck, E. Dimitrov and A. Tissen, „Applications of Cognitive Radio Systems for Industrial Wireless Automation,“ in Proc. of 4th International Conference on Cognitive Radio and Advanced Spectrum Management, New York, NY, USA, 2011.
- [9] C. Heller and C. Blumm, „A Cognitive Radio Enabled Wireless Aircraft Cabin Management System,“ in Proc. of 32nd IEEE Digital Avionics Systems Conference (DASC), 2013.
- [10] IEEE Computer Society, „IEEE Standard for Information technology - Local and metropolitan area networks - Specific requirements – Part 11: Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) Specifications Amendment 6: Wireless Access in Vehicular Environments,“ IEEE Std 802.11p-2010 (Amd. to IEEE Std 802.11-2007), pp. 1–51, July 2010.
- [11] P. Stenumgaard, J. Chilo, P. Ferrer-Coll and P. Angskog, „Challenges and Conditions for Wireless Machine-to-Machine Communications in Industrial Environments,“ in IEEE Communications Magazine, Vol. 51, Issue 6, pp. 187-192, June 2013.
- [12] M. Kloc, N. Franchi, M. Gardill and R. Weigel, „Low Latency Evaluation of an Adaptive Industrial Wireless Communications System for ISM Bands,“ in Proc. of IEEE Topical Conference on Wireless Sensors and Sensor Networks (WiSNet), 2016. *(to be published)*
- [13] B. Wang and K. Liu, „Advances in Cognitive Radio Networks: A Survey,“ in IEEE Journal of Selected Topics in Signal Processing, Vol. 5, Issue 1, pp. 5-23, February 2011.
- [14] K. Ahmad, U. Meier and S. Witte, „Predictive Opportunistic Spectrum Access using Markov Models,“ in Proc. of 17th IEEE Conference on Emerging Technologies Factory Automation (ETFA), 2012.
- [15] K. Halford and M. Webster, „Multipath Measurement in Wireless LANs,“ 2001.

**Thank You for Attention!**  
**Any Questions?**



# Appendix

## Outline

- **Optimization of Channel Selection Strategy / Prediction Algorithm**
  - Further improvement of short-real-time capability in ISM bands
  
- **Hardware Demonstrator**
  - Based on Software-Defined Radio (SDR)
  - Conceivable SDR platforms
    - Nutaq ZeptoSDR (low-cost)
    - Vector signal transceiver NI PXIe-5645R (high performance)
  - Short-real-time characterization of proposed IWC system by measurements

# Appendix

## Second Use Case

- **Wireless Transmission of Automotive Diagnostics (UDS) and Control / Calibration Data (XCP) for Hardware-in-the-Loop (HIL) based Test and Verification of Electronic Control Units (ECUs)**  
 → **Wireless Gateway (GW)**

