

Signaling Protocols and Procedures for Citizens Broadband Radio Service (CBRS): Extensions to Spectrum Access System (SAS) SAS Interface Technical Specification (Release 2)

Document WINNF-TS-3003 Version V1.1.0

30 September 2020







TERMS, CONDITIONS & NOTICES

This document has been prepared by the SSC Work Group 3 to assist The Software Defined Radio Forum Inc. (or its successors or assigns, hereafter "the Forum"). It may be amended or withdrawn at a later time and it is not binding on any member of the Forum or of the SSC Work Group 3.

Contributors to this document that have submitted copyrighted materials (the Submission) to the Forum for use in this document retain copyright ownership of their original work, while at the same time granting the Forum a non-exclusive, irrevocable, worldwide, perpetual, royalty-free license under the Submitter's copyrights in the Submission to reproduce, distribute, publish, display, perform, and create derivative works of the Submission based on that original work for the purpose of developing this document under the Forum's own copyright.

Permission is granted to the Forum's participants to copy any portion of this document for legitimate purposes of the Forum. Copying for monetary gain or for other non-Forum related purposes is prohibited.

THIS DOCUMENT IS BEING OFFERED WITHOUT ANY WARRANTY WHATSOEVER, AND IN PARTICULAR, ANY WARRANTY OF NON-INFRINGEMENT IS EXPRESSLY DISCLAIMED. ANY USE OF THIS SPECIFICATION SHALL BE MADE ENTIRELY AT THE IMPLEMENTER'S OWN RISK, AND NEITHER THE FORUM, NOR ANY OF ITS MEMBERS OR SUBMITTERS, SHALL HAVE ANY LIABILITY WHATSOEVER TO ANY IMPLEMENTER OR THIRD PARTY FOR ANY DAMAGES OF ANY NATURE WHATSOEVER, DIRECTLY OR INDIRECTLY, ARISING FROM THE USE OF THIS DOCUMENT.

Recipients of this document are requested to submit, with their comments, notification of any relevant patent claims or other intellectual property rights of which they may be aware that might be infringed by any implementation of the specification set forth in this document, and to provide supporting documentation.

This document was developed following the Forum's policy on restricted or controlled information (Policy 009) to ensure that that the document can be shared openly with other member organizations around the world. Additional Information on this policy can be found here: http://www.wirelessinnovation.org/page/Policies and Procedures.

Although this document contains no restricted or controlled information, the specific implementation of concepts contain herein may be controlled under the laws of the country of origin for that implementation. Readers are encouraged, therefore, to consult with a cognizant authority prior to any further development.

Wireless Innovation Forum TM and SDR Forum TM are trademarks of the Software Defined Radio Forum Inc.





Table of Contents

Tl	ERMS, CONDITIONS & NOTICES	ii
C	ontributors	V
1	Scope	1
2	References	
3	Definitions and abbreviations 3.1 Definitions	2
4	Release 2 Procedures and Features 4.1 Feature Capability Exchange 4.1.1 Backward and Forward Compatibility Principles of Inter-Release Operation 4.1.2 Inclusion of Feature-Specific Parameters 4.2 Enhanced CBSD Group Handling (FID: WF_ENHANCED_GROUP_HANDLING)	3 3
5	SAS-SAS Synchronization	
6	Record Encoding and Transport	5
7	Baseline Parameters of SAS-SAS Records and Extensions 7.1 SAS Feature Capability Record 7.2 CBSD Data Record 7.3 ESC Sensor Record 7.4 Zone Definition Record 7.4.1 PPA Information object 7.5 Coordination Event Record 7.5.1 CoordinationData object 7.6 Full Activity Dump Record 7.6.1 ActivityDumpFile object 7.6.2 Activity Dump File Format	6 7 14 15 16 18
8	History	20





List of Tables

Table 1: SAS Record Types and URL constructions	5
Table 2: Column Format for Release 2 Parameters	6
Table 3: SasFeatureCapability Object Definition	6
Table 4: CbsdData Object Definition	7
Table 5: RegistrationInformation Object Definition	
Table 6: GrantData Object Definition	10
Table 7: EscSensorData Object Definition	10
Table 8: EscInstallationParam object	11
Table 9: RadiationPattern object	13
Table 10: ZoneData Object Definition	14
Table 11: PPAInformation Object Definition	15
Table 12: CoordinationEvent object	16
Table 13: CoordinationData Object Definition	18
Table 14: FullActivityDump object	
Table 15: ActivityDumpFile object	18
Table 16: MessageAggregation Object Definition	19





Contributors

The following individuals made significant contributions to this document:

Editor: Yi Hsuan (Google)

Group Chair: Navin Hathiramani (Nokia)

Other Member Representatives:

- Sho Furuichi (Sony Corporation)
- Ariful Hannan (CommScope)
- Masoud Olfat (Federated Wireless)



Extensions to Spectrum Access System (SAS) - SAS Interface Technical Specification (Release 2)

1 Scope

This document is a Technical Specification that extends the SAS-SAS interface [n.1] to support Release 2 features and procedures. Some features, data objects and parameters defined in [n.1] are deprecated in the Release 2 SAS-SAS interface, including

- Time-range request support (Section 6.1 in [n.1])
- By-ID request support (Section 6.2 in [n.1])
- Push support (Section 6.3 in [n.1])
- SasAdministrator object (Section 8.1 in [n.1])
- SasImplementation object (Section 8.2 in [n.1])
- *terminated* parameter (Section 8.3 and 8.5 in [n.1])
- groupingParam parameter (Section 8.3.1 in [n.1])

The key words "required", "shall", "shall not", "should", "should not", "recommended", "may", and "optional" in this document are to be interpreted as described in RFC 2119 [n.2]. In addition, the key word "conditional" shall be interpreted to mean that the definition is an absolute requirement of this specification only if the stated condition is met.

2 References

2.1 Normative references

The following referenced documents are necessary for the application of the present document.

- [n.1] WINNF-TS-0096 V1.3.1, "Signaling Protocols and Procedures for Citizens Broadband Radio Service (CBRS): Spectrum Access System (SAS) - SAS Interface Technical Specification", Wireless Innovation Forum
- [n.2] RFC-2119, "Key words for use in RFCs to Indicate Requirement Levels", March 1997
- [n.3] WINNF-SSC-0011, "Spectrum Sharing Committee Policy and Procedure SSC Abbreviations and Definitions", Wireless Innovation Forum
- [n.4] WINNF-SSC-0008, "Coordinated Periodic Activities Policy", Wireless Innovation Forum
- [n.5] <u>RFC-7159</u>, "The JavaScript Object Notation (JSON) Data Interchange Format", March 2014
- [n.6] <u>RFC-2616</u>, Hypertext Transfer Protocol -- HTTP/1.1, Fielding, Gettys, Mogul, Frystyk, Masinter, Leach and Berners-Lee, June 1999
- [n.7] WINNF-TS-0112, "Requirements for Commercial Operation in the U.S. 3550-3700 MHz Citizens Broadband Radio Service Band", Wireless Innovation Forum
- [n.8] RFC-3339, "Date and Time on the Internet: Timestamps", July 2002
- [n.9] WINNF-TS-0016 V1.2.4, "Signaling Protocols and Procedures for Citizens Broadband Radio Service (CBRS): Spectrum Access System (SAS) - Citizens Broadband Radio Service Device (CBSD) Interface Technical Specification", Wireless Innovation Forum
- [n.10] RFC-7946, The GeoJSON Format, Butler et. al., August 2016





- [n.11] WINNF-TS-0245, "Operations for Citizens Broadband Radio Service (CBRS): Priority Access Licensee (PAL) Database Technical Specification", Wireless Innovation Forum
- [n.12] NGA.STND.0036_1.0.0_WGS84 (Version 1.0.0 July 8, 2014): Department of Defense (DoD) World Geodetic System (WGS) 1984
- [n.13] RFC 7233, "Hypertext Transfer Protocol (HTTP/1.1): Range Requests", June 2014
- [n.14] <u>RFC-4627</u>, The application/json Media Type for JavaScript Object Notation (JSON), Crockford, July 2006
- [n.15] WINNF-SSC-0013, "WInnForum Registry of CBRS Vendor/Admin IDs for Third-Party Proprietary Feature Prefixes", Wireless Innovation Forum
- [n.16] WINNF-SSC-0010, "WInnForum Recognized CBRS Grouping Parameters Document", Wireless Innovation Forum
- [n.17] WINNF-TS-3002, "Signaling Protocols and Procedures for Citizens Broadband Radio Service (CBRS): Extensions to Spectrum Access System (SAS) - Citizens Broadband Radio Service Device (CBSD) Interface Technical Specification (Release 2)", Wireless Innovation Forum
- [n.18] WINNF-TS-1001, "CBRS Operational and Functional Requirements (Release 2)", Wireless Innovation Forum

3 Definitions and abbreviations

3.1 Definitions

In addition to definitions in [n.3], the following definitions are also used in this document.

Feature ID: A string identifying the name of a Release 2 feature. Feature IDs applicable to this specification are WInnForum-defined Feature IDs included in this document or third-party proprietary Feature IDs.

Non-Regulatory Impacting Feature Capability List: A list of Feature IDs representing all operationally supported features of a SAS that do not impact Part 96 regulatory compliance.

Regulatory Impacting Feature Capability List: A list of Feature IDs representing all operationally supported features of a SAS that could impact Part 96 regulatory compliance.

3.2 Abbreviations

In addition to abbreviations specified in [n.3], the following abbreviations are also used in this document.

FID Feature ID





4 Release 2 Procedures and Features

4.1 Feature Capability Exchange

This section defines feature capability exchange procedure which ensures backward and forward compatibility between operations between different releases of SASs. Section 4.1.1 provides backward and forward compatibility principles of inter-release operation. Section 4.1.2 describes how a SAS should treat feature-specific parameters received from a peer SAS. Feature Capability Exchange shall facilitate the exchange of both WInnForum defined Feature IDs and proprietary Feature IDs. WInnForum defined Feature IDs (starting with "WF_") are specified in this document starting with section 4.2. Third party proprietary Feature IDs shall be prefixed with CBRS vendor/administrator IDs registered in WINNF-SSC-0013 [n.15].

4.1.1 Backward and Forward Compatibility Principles of Inter-Release Operation

To allow predictable operation between SASs supporting different releases of SAS-SAS protocols, the SAS-SAS protocol in this specification is designed to be backward and forward compatible. To ensure backward compatibility, any SAS beyond Release 1 shall exchange the Non-Regulatory Impacting Feature Capability List and the Regulatory Impacting Feature Capability List in the synchronization process as described in Section 5. A feature operationally supported by a SAS shall be included in the Non-Regulatory Impacting Feature Capability List if the SAS uses the feature in a way that does not impact Part 96 regulatory compliance. A feature operationally supported by a SAS shall be included in the Regulatory Impacting Feature Capability List if the SAS uses the feature in a way that could impact Part 96 regulatory compliance.

A SAS shall ignore unrecognized feature names in the Feature Capability Lists and unrecognized parameters associated with features it doesn't support received from a peer SAS. If a SAS does not receive the Feature Capability Lists from a peer SAS, the peer SAS shall be treated as a Release 1 SAS.

4.1.2 Inclusion of Feature-Specific Parameters

Feature specific parameters are always Conditional or Optional and are identified with the corresponding feature names. A SAS shall ignore a parameter received from a peer SAS if the parameter name is unrecognized or the SAS does not support the feature associated with the parameter.

4.2 Enhanced CBSD Group Handling (FID: WF ENHANCED GROUP HANDLING)

This feature supports CBSD grouping information exchange using the SAS-CBSD and the SAS-SAS interfaces. This feature does not impact Part 96 regulatory compliance.

This feature does not define how to use CBSD grouping information but only allows the exchange of grouping information. Depending on specific grouping information, it may be





necessary for a SAS to share the information with peer SASs through the SAS-SAS interface. By using this feature, a SAS may optionally share the CBSD grouping information with peer SASs by including the *GroupParam* object and/or the *GroupConfig* object in the *CbsdData* Object, as defined in Table 4.

4.3 Enhanced Antenna Pattern (FID: WF_ENH_ANTENNA_PATTERN)

This feature enables the use of enhanced antenna patterns to allow more efficient use of the CBRS spectrum in accordance with requirements and applicable use cases provided in Annex 5 of WINNF-TS-1001[n.18]. This feature can be used as non-regulatory impacting and/or regulatory impacting depending on use cases.

A SAS operationally supporting this feature shall include *antennaVerticalBeamwidth* and/or *antennaModel*, as defined in WINNF-TS-3002 [n.17], in *installationParam* in Table 5 if *antennaVerticalBeamwidth* and/or *antennaModel* are available for a CBSD. A SAS operationally supporting this feature shall perform operations according to requirements defined in the Annex 5 of WINNF-TS-1001[n.18].

4.4 CPE-CBSD Indicator (FID: WF_CPE_CBSD_INDICATOR)

This feature allows the CBSD to indicate to the SAS whether it is a CPE-CBSD by setting the *cpeCbsdIndication* parameter in the CBSD Registration Procedure or in the Feature Capability Exchange Procedure [n.17]. This feature does not impact Part 96 regulatory compliance.

A SAS operationally supporting this feature shall include *cpeCbsdIndication* in Table 4 if *cpeCbsdIndication* is available for the CBSD.

5 SAS-SAS Synchronization

5.1 Full Activity Dump

At a period specified in [n.4], the SAS shall generate a Full Activity Dump comprised of activity dump files corresponding to the SAS Feature Capability Record, qualifying CBSD Data Records, Zone Data Records, and ESC Sensor Records. A SAS shall provide information on accessing activity dump files through the URL in Table 1.

In particular, records in Full Activity Dump shall include:

- SAS Feature Capability Record, which includes the Non-Regulatory Impacting Feature Capability List and the Regulatory Impacting Feature Capability List;
- CBSD Data Records for CBSDs which have at least one Grant. For those CBSDs, all Grants shall be included.;
- Zone Data Records including PPA data;





- ESC Sensor Records which include information of ESC sensors affiliated with the SAS;
- Coordination Event Records which include coordination information that shall be shared among SASs.

The dump data itself shall also be made available for at least 14 days.

Release 2 compliant SASs shall always include the SAS Feature Capability Record in Full Activity Dump data. If Full Activity Dump data retrieved from a peer SAS does not include the SAS Feature Capability Record, the peer SAS shall be considered a Release 1 SAS.

6 Record Encoding and Transport

6.1 Record Encoding

SAS-SAS Records shall be encoded using JSON (JavaScript Object Notation) as defined in RFC-7159 [n.5].

6.2 Record Transport

The HTTP GET method shall be used for all SAS-SAS requests. The URL endpoints for SAS-SAS requests are described in Table 1. A SAS administrator may choose to use the same or different \$BASE_URL in Table 1 for transporting records defined in different releases of SAS-SAS protocols. A SAS administrator shall ensure that all operational URLs are able to properly receive and respond to requests from peer SASs supporting different releases of SAS-SAS protocols pursuant to the backward and forward compatibility principles described in section 4.1.1.

Table 1: SAS Record Types and URL constructions

SAS Record Type	sas_record_type	URL construction
SAS Feature	sas_feature	Not applicable
Capability		
CBSD Data	cbsd	Not applicable
ESC Sensor Data	esc_sensor	Not applicable
Zone Data	zone	Not applicable
Coordination	coordination	Not applicable
events		
Full Activity	dump	HTTP request: GET \$BASE_URL/dump
Dump		Return type: FullActivityDump object (See
		7.6)





7 Baseline Parameters of SAS-SAS Records and Extensions

In this section, parameters of SAS-SAS records are described in more detail. A parameter value can be one of the primitive JSON data types (string, number, boolean, array, or object). If a parameter is an object, a name for the object is given and a separate table describes parameters in the object.

Each parameter is indicated as "Required", "Optional" or "Conditional". The definitions of these indicators are as follows:

"Required": The parameter shall always be included in the object it belongs to.

"Optional": The parameter may be included in the object it belongs to.

"Conditional": The parameter shall be included in the object it belong to, if and only

if the specified conditions are satisfied.

The tables of parameters in this section have a column marked R/O/C that indicates whether the particular parameter is "Required", "Optional", or "Conditional".

The JSON objects specified in the following subsections are conformant with RFC-4627 [n.14]. Note that this means that Unicode characters are used and have a default encoding of UTF-8.

Feature-specific parameters shall be described with the following column format:

Table 2: Column Format for Release 2 Parameters

Parameter		
NAME: [Name of extension parameter]		
DATA TYPE : [One of JSON Data Types specified in section 7]		
FEATURE ID : [Feature ID(s) or <i>Mandatory</i>]		

The label "**FEATURE ID**" describes in which specific features this parameter is used. The values are WInnForum defined FIDs or "*Mandatory*", where "*Mandatory*" means that the parameter does not depend on specific-features and shall be supported for Release 2 operation.

Any parameter which does not have the "FEATURE ID" label is specified in WINNF-TS-0096 [n.1] and its description is reproduced here <u>for information only.</u>

7.1 SAS Feature Capability Record

Table 3: SasFeatureCapability Object Definition

Parameter	R/O/C	Parameter Information
NAME: id DATA TYPE: string FEATURE ID: Mandatory	Required	• Format: sas_feature/\$ADMINISTRATOR_ID \$ADMINISTRATOR_ID is a unique SAS administrator identifier.





Parameter NAME: nonRegFeatureCapabilityList DATA TYPE: array of string FEATURE ID: Mandatory	R/O/C Required	Parameter Information This parameter represents SAS's Non-Regulatory Impacting Feature Capability List which may contain zero or more FIDs.
NAME: regFeatureCapabilityList DATA TYPE: array of string FEATURE ID: Mandatory	Required	This parameter represents SAS's Regulatory Impacting Feature Capability List which may contain zero or more FIDs.

7.2 CBSD Data Record

This section defines *CbsdData* Object for Release 2 CBSDs. See details in WINNF-TS-0016 [n.9] for creation of Release 1 CBSD Data Record.

Table 4: CbsdData Object Definition

Tu	bie 4. CosaDaia Objec	et Definition
Parameter	R/O/C	Parameter Information
NAME: id	Required	• Format:
DATA TYPE : string	1	cbsd/\$CBSD_REFERENCE_ID
		\$CBSD_REFERENCE_ID is defined as \$FCC_ID + "/" +
		sha1(\$SERIAL_NUMBER).
		\$FCC_ID and \$SERIAL_NUMBER are the unescaped <i>fccId</i> and <i>cbsdSerialNumber</i> strings of the CBSD registered during the CBSD Registration Procedure [n.9].
		SHA-1 is applied to the unescaped <i>cbsdSerialNumber</i> string with no additional line termination characters.
NAME: registration	Required	This parameter contains the registration
DATA TYPE : object:	1	information of the CBSD associated with
RegistrationInformation		the <i>id</i> parameter.
NAME: grants	Required	An array of one or more data object that
DATA TYPE : array of object:	•	contains the information of Grants of the
GrantData		CBSD associated with the <i>id</i> parameter.





Parameter	R/O/C	Parameter Information
NAME: groupingParam DATA TYPE: array of object: GroupParam FEATURE ID: WF_ENHANCED_GROUP_H ANDLING	Optional	An array of data objects that contains the information about the Group(s) currently associated with that CBSD. See details of <i>GroupParam</i> object definition in WINNF-TS-3002 [n.17].
NAME: groupingConfig DATA TYPE: array of object: GroupConfig FEATURE ID: WF_ENHANCED_GROUP_H ANDLING	Optional	An array of data objects that includes information concerning group configuration currently associated with the CBSD. See details of <i>GroupConfig</i> object definition in WINNF-TS-3002 [n.17].
NAME: cpeCbsdIndication DATA TYPE: boolean FEATURE ID: WF_CPE_CBSD_INDICATOR	Conditional	This parameter, when set to TRUE, indicates the CBSD is a CPE-CBSD. The value FALSE indicates the CBSD is not a CPE-CBSD. This parameter shall be included if its value is available for a CBSD.

Table 5: RegistrationInformation Object Definition

Tubic 5. Registration Hydriation Object Definition		
Parameter	R/O/C	Parameter Information
NAME: userId DATA TYPE: string	Optional	This parameter contains a User Registration ID (UR-ID) of the CBSD that was registered to the SAS Implementation.
NAME: fccId DATA TYPE: string	Required	This parameter contains a FCC ID of the CBSD that was registered to the SAS Implementation.
NAME: cbsdSerialNumber DATA TYPE: string	Optional	This parameter contains a serial number of the CBSD that was registered to the SAS Implementation.
NAME: callSign DATA TYPE: string	Optional	This parameter contains a call sign of the CBSD User of the CBSD that was registered to the SAS Implementation.





Parameter	R/O/C	Parameter Information
NAME: cbsdCategory DATA TYPE: string	Required	This parameter contains the category of the CBSD that was registered to the SAS Implementation.
NAME: cbsdInfo DATA TYPE: object: CbsdInfo	Optional	A data object that contains CBSD model information that was registered to the SAS Implementation. See details of <i>CbsdInfo</i> object definition in WINNF-TS-3002 [n.17].
NAME: installationParam DATA TYPE: object: InstallationParam	Required	A data object that contains all the installation parameters of the CBSD that were registered to the SAS Implementation. All of the parameters, specified in the <i>InstallationParam</i> object, that were registered to the SAS Implementation shall be included in this object. See details of <i>InstallationParam</i> object definition in WINNF-TS-3002 [n.17].
NAME: airInterface DATA TYPE: object: AirInterface	Required	A data object that contains air interface information of the CBSD that were registered to the SAS Implementation. All of the parameters, specified in the <i>AirInterface</i> object, that were registered to the SAS Implementation shall be included in this object. See details of <i>AirInterface</i> object definition in WINNF-TS-3002 [n.17].
NAME: measCapability DATA TYPE: array of string	Required	This parameter contains the measurement capability of the CBSD that were registered to the SAS Implementation.





Table 6: GrantData Object Definition

Parameter	R/O/C	Parameter Information
NAME: id DATA TYPE: string	Required	A Grant identifier unique to this Grant and CBSD allowing peer SASs to identify the Grant.
NAME: operationParam DATA TYPE: object: OperationParam	Required	This data object includes operation parameters associated with the approved Grant. See details of <i>OperationParam</i> object
NAME: requestedOperationParam DATA TYPE: object: OperationParam	Required	definition in WINNF-TS-3002 [n.17]. This data object includes operation parameters that were requested for the Grant by the CBSD during the CBSD Grant Procedure.
		See details of <i>OperationParam</i> object definition in WINNF-TS-3002 [n.17].
NAME: channelType DATA TYPE: string	Required	Channel type of the Grant. The acceptable values are: "PAL": the channel is a PAL channel. "GAA": the frequency range is for GAA use.
NAME: grantExpireTime DATA TYPE: string	Required	Indicates the UTC time when the Grant expires. Format: YYYY-MM-DDThh:mm:ssZ [n.8]

7.3 ESC Sensor Record

Table 7: EscSensorData Object Definition

	1. Escochsor Data Obj.	
Parameter	R/O/C	Parameter Information
NAME: id DATA TYPE: string	Required	• Format: esc_sensor/\$ADMINISTRATOR_
		ID/\$SENSOR_ID \$ADMINISTRATOR_ID is the a
		unique SAS Administrator identifier. \$SENSOR_ID is a unique identifier
		for the referenced ESC Sensor created by the ESC Operator.
NAME: installationParam	Required	Contains ESC Sensor installation
DATA TYPE : object: EscInstallationParam		parameters





Parameter	R/O/C	Parameter Information
NAME: protectionLevel DATA TYPE: number	Optional	The protection level to be applied to this ESC Sensor in units of dBm/MHz. If not present, the default value of the protection level specified in [n.7] shall be applied to the ESC Sensor associated with the <i>id</i> parameter.

Table 8: EscInstallationParam object

	able 8: EscInstallation	
Parameter	R/O/C	Parameter Information
NAME: latitude DATA TYPE: number	Required	Latitude of the ESC antenna location in degrees relative to the WGS 84 datum [n.12]. The allowed range is from -90.000000 to +90.000000. Positive values represent latitudes north of the equator; negative values south of the equator. Values are specified using 6 digits to the right of the decimal point.
NAME: longitude DATA TYPE: number	Required	Longitude of the ESC antenna location in degrees relative to the WGS84 datum [n.12]. The allowed range is from -180.000000 to +180.000000. Positive values represent longitudes east of the prime meridian; negative values west of the prime meridian. Values are specified using 6 digits to the right of the decimal point.
NAME: height DATA TYPE: number	Required	This parameter contains the ESC antenna height in meters that may be expressed as an integer or as a numeric value including a decimal point. When the <i>heightType</i> parameter value is "AGL", the antenna height should be given relative to ground level. When the <i>heightType</i> parameter value is "AMSL", it is given with respect to WGS84 datum.





Parameter	R/O/C	Parameter Information
NAME: heightType DATA TYPE: string	Required	The value should be "AGL" or "AMSL". AGL height is measured relative to the ground level. AMSL height is measured relative to the mean sea level.
NAME: antennaAzimuth DATA TYPE: number	Required	This parameter contains the boresight direction of the horizontal plane of the ESC antenna in degrees with respect to true north. The value of this parameter is an integer with a value between 0 and 359 inclusive. A value of 0 degrees means true north; a value of 90 degrees means east.
NAME: antennaDowntilt DATA TYPE: number	Required	If present, this parameter contains the ESC antenna down tilt in degrees and is an integer with a value between -90 and +90 inclusive; a negative value means the antenna is tilted up (above horizontal).
NAME: azimuthRadiationPattern DATA TYPE: array of object: RadiationPattern	Required	This parameter specifies an ESC antenna radiation pattern or an effective ESC antenna radiation pattern in any direction in the azimuthal plane, specified at 1 degree increments referenced to the antenna boresight direction.
NAME: elevationRadiationPattern DATA TYPE: array of object: RadiationPattern	Required	If present, this parameter specifies an ESC antenna radiation pattern or an effective ESC antenna radiation pattern in any direction in the elevation plane (orthogonal to the azimuthal plane).





Table 9: RadiationPattern object

Parameter	R/O/C	Parameter Information
NAME: angle	Required	This is the radiation angle.
DATA TYPE: number		In the azimuth plane: the value is given in degrees relative to the antenna boresight direction. The value of this parameter is an integer, increasing in the clockwise direction as viewed from above, between 0 and 359 inclusive.
		In the elevation plane: the angle is given in degrees relative to the horizon. The value of this parameter is an integer between -180 and 180 inclusive. Radiation below the horizon has a positive elevation angle and radiation above the horizon has a negative elevation angle.
NAME: gain DATA TYPE: number	Required	The radiation gain in dBi. This parameter is an integer with a value between -127 and +128 (dBi). The gain provided is the gain in the direction of 'angle'.





7.4 Zone Definition Record

Table 10: ZoneData Object Definition

	I	du Object Demintion
Parameter	R/O/C	Parameter Information
NAME: id	Required	• Format : zone/\$CREATOR/\$ZONE_ID
DATA TYPE : string	_	_
_		When the <i>usage</i> parameter is equal to
		"PPA", the format of the \$CREATOR string
		is "ppa/\$ADMINISTRATOR_ID" and the
		\$ZONE_ID is equal to the PPA-ID string.
		When the <i>usage</i> parameter is equal to
		"CENSUS_TRACT" the format of the
		\$CREATOR string is
		"census_tract/census/\$YEAR" and the
		\$ZONE_ID is equal to the FIPS code of the
		census tract. \$YEAR is equal to the census
		year in which the census tract was defined.
		Note: this zone type exchange is optional.
		When the <i>usage</i> parameter is equal to
		"EXCLUSION_ZONE" the format of the
		\$CREATOR string is
		"exclusion_zone/ntia/\$DATE", and \$DATE
		is a "YYYY_MM_DD" string describing the
		date on which NTIA issued the definition of
		the exclusion zone. \$ZONE_ID is a unique
		reference identifier of an exclusion zone.
NAME: name	Optional	Human-readable local significant string. The
DATA TYPE : string		name of this zone.





Parameter	R/O/C	Parameter Information
NAME: creator DATA TYPE: string	Optional	This parameter contains the creator of the Zone Data associated with the \$ZONE_ID. The value of this parameter shall be used as \$CREATOR in the <i>id</i> parameter. The value of \$CREATOR shall be ppa/\$ADMINISTRATOR_ID if the value of the <i>usage</i> parameter is "PPA". The value of \$CREATOR shall be exclusion_zone/ntia/\$DATE if the value of the <i>usage</i> parameter is "EXCLUSION_ZONE", where \$DATE is expressed by using the format, YYYY_MM_DD, describing the date on which NTIA issued the definition of the exclusion zone. The value of \$CREATOR shall be census_tract/census/\$YEAR if the value of
NAME: usage DATA TYPE: string	Required	the <i>usage</i> parameter is "CENSUS_TRACT", where \$YEAR is equal to the census year in which the census tract was defined. This parameter describes the usage (i.e. type of zone) of the zone data. One of the following shall be included: • CENSUS_TRACT • PPA • EXCLUSION ZONE
NAME: ppaInfo DATA TYPE: object: PPAInformation	Conditional	if the <i>usage</i> parameter is equal to "PPA", this parameter shall be included.
NAME: zone DATA TYPE: object: GeoJSON	Required	Self-contained geometry description of the addressed zone data [n.10]. See details in Normative Annex B of WINNF-TS-0096 [n.1]

7.4.1 PPA Information object

Table 11: PPAInformation Object Definition

Parameter	R/O/C	Parameter Information





NAME: palId	Required	List of one or more PAL Database Record
DATA TYPE : array of	-	IDs (ref: [n.11]) upon which the PPA is
string		based. All PALs indicated in this parameter
_		shall have a single PAL Holder.
NAME: cbsdReferenceId	Required	List of one or more CBSD Reference IDs in
DATA TYPE : array of	_	the cluster list of the PPA.
string		
		The format of CBSD Reference ID shall
		follow the definition of <i>id</i> parameter in
		CbsdData object.
NAME: ppaBeginDate	Required	Date of the start of the PPA protection
DATA TYPE : string		period.
		Format: YYYY-MM-DDThh:mm:ssZ [n.5]
NAME:	Required	This field represents the PPA expiration
ppaExpirationDate		date.
DATA TYPE : string		Format: YYYY-MM-DDThh:mm:ssZ [n.5]
NAME : ppaRegionType	Required	This field describes the region type of the
DATA TYPE : string		PPA to be used in calculating the path loss
		for PPA protection. The field shall be set to
		one of the following values:
		• "URBAN"
		• "SUBURBAN"
		• "RURAL"

7.5 Coordination Event Record

Table 12: CoordinationEvent object

	14510 121 000	nananonEveni object
Parameter	R/O/C	Parameter Information
NAME: id	Required	• Format:
DATA TYPE : string	_	coordination/\$ADMINISTRATOR_ID/\$EVE
_		NT_ID
		\$ADMINISTRATOR_ID is a SAS
		Administrator ID.
		\$EVENT_ID is Coordination Event record ID
		created by the originating SAS Administrator.
NAME: name	Optional	Human-readable local unique reference to the
DATA TYPE : string		Coordination Event Record.
NAME: creator	Optional	Human-readable string identifying the creator of
DATA TYPE : string		the Coordination Event Record.
NAME: creationDate	Required	This parameter is the date the Coordination Event
DATA TYPE : string	_	Record was created.
		Format: YYYY-MM-DDThh:mm:ssZ [n.8]





Parameter	R/O/C	Parameter Information
NAME: expirationDate DATA TYPE: string	Required	This parameter is the expiration date of the Coordination Event Record. Format: YYYY-MM-DDThh:mm:ssZ [n.8]
NAME: description DATA TYPE: string	Optional	Human-readable description of the Coordination Event Record.
NAME: coordinationType DATA TYPE: string	Required	This parameter is the type of the Coordination Event Record. One of the following values shall be included: INTERFERENCE_REPORT AD_HOC_EXCLUSION_ZONE ENFORCEMENT_ACTION ESC_SENSOR_DEPLOYMENT
NAME: coordinationDevice DATA TYPE: array of string	Conditional	This parameter contains one or more IDs of the device involved in the Coordination Event Record. Acceptable values of the element of this parameter is as follows: • The value of the <i>id</i> parameter of the <i>CbsdData</i> object • The value of the <i>id</i> parameter of the <i>EscSensorData</i> object • Identifier of a specific incumbent device This parameter shall be included if the <i>coordinationType</i> parameter is set to "ESC_SENSOR_DEPLOYMENT" or "INTERFERENCE REPORT".
NAME: coordinationZone DATA TYPE: array of string	Conditional	This parameter contains one or more IDs of the Zone Data involved in the Coordination Event Record. This parameter shall be included if the coordinationType parameter is set to "AD HOC EXCLUSION ZONE".
NAME: coordinationData DATA TYPE: object: CoordinationData	Optional	This parameter is an object that contains the event-specific data.





7.5.1 CoordinationData object

Table 13: CoordinationData Object Definition

Parameter	R/O/C	Parameter Information
The contents of this object are FFS.		

7.6 Full Activity Dump Record

Table 14: FullActivityDump object

Table 14. FunActivityDump object		
Parameter	R/O/C	Parameter Information
NAME: files DATA TYPE: array of object: ActivityDumpFile	Required	Array of one or more objects corresponding to files comprising the Full Activity Dump data.
NAME: generationDateTime DATA TYPE: string	Required	The date and time at which the Full Activity Dump data was generated. Format: YYYY-MM-DDThh:mm:ssZ [n.8]
NAME: description DATA TYPE: string	Optional	Any additional human-readable description the source SAS may wish to attach.

7.6.1 ActivityDumpFile object

Table 15: ActivityDumpFile object

Parameter	R/O/C	Parameter Information
NAME: url	Required	The retrieval URLs at which the peer SAS
DATA TYPE : string	1	can retrieve the activity dump file.
_		Retrieval of the resources at these URLs
		shall support byte-range requests using the
		HTTP Content-Range mechanisms [n.13].
NAME: checksum	Required	The SHA-1 checksum of the contents of
DATA TYPE : string		the activity dump file referred to by <i>url</i> .
NAME: size	Required	The size of the activity dump file in bytes.
DATA TYPE : number		
NAME: version	Required	The version of the SAS-SAS protocol used
DATA TYPE : string		for generating this file.
_		The value of this string shall be "v2.0".





Parameter	R/O/C	Parameter Information
NAME: recordType DATA TYPE: string	Required	The type of records contained in the activity dump file The value of this parameter shall be one of the sas_record_type values as defined in Table 1. Examples: "sas feature", "zone", "cbsd",
		"coordination"

7.6.2 Activity Dump File Format

The activity dump file retrieved from the *url* field specified in the *ActivityDumpFile* object is composed of a *MessageAggregation* Object as defined in Table 16.

Table 16: MessageAggregation Object Definition

Parameter	R/O/C	Parameter information
NAME: recordData	Required	An array of zero or more SAS record(s)
DATA TYPE : array of object		with the same record type, as specified in
		recordType of the corresponding
		ActivityDumpFile object.





8 History

Document history				
V1.0.0	2 April 2020	Initial version balloted and approved for publication		
V1.1.0	30 September 2020	Technical revision addressing numerous change requests		