



**Signaling Protocols and Procedures for
Citizens Broadband Radio Service (CBRS):
WinnForum Recognized
CBRS Air Interfaces and Measurements**

Document WINNF-SSC-0002

Version 3.0.1

1 October 2018



Table of Contents

1	Introduction	4
2	Scope	4
3	References	4
3.1	Normative references	4
3.2	Informative references	4
4	Definitions and abbreviations	4
5	Version Compatibility	5
6	Registered CBRS Air Interfaces	5
6.1	E_UTRA	5
6.2	CAMBIUM_NETWORKS	5
6.3	4G_BBW_SAA_1	5
7	Measurement Report Types	5
7.1	Received Power	5
7.1.1	RECEIVED_POWER_WITHOUT_GRANT	5
7.1.2	RECEIVED_POWER_WITH_GRANT	6
8	Document History	8

List of Tables

Table 1: <i>MeasReport</i> Object Definition.....	6
Table 2: <i>RcvdPowerMeasReport</i> Object Definition	7

WinnForum Recognized CBRS Air Interfaces and Measurements

1 Introduction

This document lists information about the air interfaces (AI) and measurement types supported by the standards developed by the Wireless Innovation Forum for the Citizens Broadband Radio Service (CBRS) band.

2 Scope

This document consolidates information registered with the Wireless Innovation Forum following policy WINNF-17-SSC-0001 [n.4]. This document provides a list of the AIs, references for those AIs, and information about measurements that can be made by Citizens Broadband Radio Service Devices (CBSDs).

3 References

3.1 Normative references

The following referenced documents are necessary for the application of the present document.

- [n.1] “CBRS Communications Security Technical Report”, WINNF-15-P-0065, Version V1.0.0, 2 August 2016.
- [n.2] [RFC-2119](#), “Key words for use in RFCs to Indicate Requirement Levels”, March 1997.
- [n.3] “Spectrum Access System (SAS) - Citizens Broadband Radio Service Device (CBSD) Interface Technical Specification”, WINNF-16-S-0016 V2.0.0.
- [n.4] “Spectrum Sharing Committee Policy and Procedure: CBRS Air Interface and Measurement Registration”, WINNF-17-SSC-0001, Version 1.0.0, 18 April 2017

3.2 Informative references

The following referenced documents are not necessary for the application of the present document but they assist the reader with regard to a particular subject area.

- [i.1] Report and Order and Second Further Notice of Proposed Rulemaking, Amendment of the Commission’s Rules with Regard to Commercial Operations in the 3550-3650 MHz Band, GN Docket No. 12-354, Federal Communications Commission, 21 April 2015.
- [i.2] Order on Reconsideration and Second Report and Order, Amendment of the Commission’s Rules with Regard to Commercial Operations in the 3550-3650 MHz Band, GN Docket No. 12-354, Federal Communications Commission, 2 May 2016.

4 Definitions and abbreviations

AI: Air Interface

CBRS: Citizens Broadband Radio Service.

CBRS band: The 3550-3700 MHz Citizens Broadband Radio Service band.

Citizens Broadband Radio Service Device (CBSD): Fixed Stations, or networks of such stations, that operate on a Priority Access or General Authorized Access basis in the Citizens Broadband Radio Service.

E-UTRA: Evolved Universal Terrestrial Radio Access

Spectrum Access System (SAS): A system that authorizes and manages use of spectrum for the Citizens Broadband Radio Service in accordance with subpart F in [n.8].

5 Version Compatibility

Version 1 of this document is compatible with:

- V1.1.0 of [n.3].

6 Registered CBRS Air Interfaces

The following air interfaces (AIs) have been registered with the Wireless Innovation Forum for operation in the CBRS band:

6.1 E_UTRA

- Air Interface Reference: [3GPP TS 36.300](#)

6.2 CAMBIUM_NETWORKS

6.3 4G_BBW_SAA_1

- Air Interface Reference: IEEE 802.16e

7 Measurement Report Types

The following measurement types have been registered with the Wireless Innovation Forum for operation in the CBRS band.

7.1 Received Power

Definition: Measurement of the radio frequency energy received over a set of frequency ranges during a measurement interval with results reported to a SAS for each of the frequency ranges in terms of effective received power for each frequency range.

The measurement capabilities associated with the Received Power measurement type are given in the following subsections.

7.1.1 RECEIVED_POWER_WITHOUT_GRANT

Semantics: Received Power can be measured and reported when the CBSD does not have a spectrum grant from the SAS. If this measurement report capability is indicated by the SAS to the CBSD, the CBSD performs and reports Received Power measurements over the entire CBRS

band in segments that do not exceed 10 MHz per measurement report. Those measurement reports are sent to the SAS in the first Spectrum Inquiry Request message and first Grant Request message.

Table 1: *MeasReport* Object Definition

Parameter	Description
NAME: <i>rcvdPowerMeasReports</i> DATA TYPE: array of object: <i>RcvdPowerMeasReport</i>	An array of separate reports measured as Received Power.

Table 2: *RcvdPowerMeasReport* Object Definition

Parameter	Description
NAME: <i>measFrequency</i> DATA TYPE: number	Frequency of the lowest end of the measured frequency range in Hz.
NAME: <i>measBandwidth</i> DATA TYPE: number	Measurement bandwidth in Hz used by CBSD to perform the Received Power measurement. The range bounded by <i>measFrequency</i> as the lower bound and (<i>measFrequency</i> + <i>measBandwidth</i>) as the upper bound expresses the frequency range used in making the measurement.
NAME: <i>measRcvdPower</i> DATA TYPE: number	Received Power measurement in units of dBm. The range of this parameter is -100 dBm .. -25dBm. The Received Power is measured over the frequency range from <i>measFrequency</i> as the lower bound to (<i>measFrequency</i> + <i>measBandwidth</i>) as the upper bound.

7.1.2 RECEIVED_POWER_WITH_GRANT

Semantics: Received Power can be measured and reported when the CBSD has a spectrum grant from the SAS. If this measurement report capability is indicated by the SAS to the CBSD, the CBSD performs and reports Received Power measurements over one or more frequency ranges that do not exceed 10 MHz per measurement report. The measurement report(s) are sent to the SAS in the subsequent Heartbeat Request message.

Table 3: *MeasReport* Object Definition

Parameter	Description
NAME: <i>rcvdPowerMeasReports</i> DATA TYPE: array of object: <i>RcvdPowerMeasReport</i>	An array of separate reports measured as Received Power.

Table 4: RcvdPowerMeasReport Object Definition

Parameter	Description
NAME: <i>measFrequency</i> DATA TYPE: number	Frequency of the lowest end of the measured frequency range in Hz.
NAME: <i>measBandwidth</i> DATA TYPE: number	Measurement bandwidth in Hz used by CBSD to perform the Received Power measurement. The range bounded by <i>measFrequency</i> as the lower bound and (<i>measFrequency</i> + <i>measBandwidth</i>) as the upper bound expresses the frequency range used in making the measurement.
NAME: <i>measRcvdPower</i> DATA TYPE: number	Received Power measurement in units of dBm. The range of this parameter is -100 dBm .. -25dBm. The Received Power is measured over the frequency range from <i>measFrequency</i> as the lower bound to (<i>measFrequency</i> + <i>measBandwidth</i>) as the upper bound.

8 Document History

Document history		
V1.0.0	19 April 2017	Initial version
V2.0.0	22 June 2017	Added air interface from Cambium Networks. Corrected E_UTRA to reflect modified rules.
V2.0.1	22 June 2017	Editorial changes
V2.0.2	30 August 2017	Updated the version number of the SAS-CBSD TS according to the new numbering method.
V3.0.0	15 August 2018	Added 4G_BBW_SAA_1 air interface submitted by Siemens
V3.0.1	1 October 2018	Corrected copyright date and updated this table to include V3.0.0